

**SPKR-SFL-32
SPKR-SFL-40
SPKR-SFL-46**
Optional Accessory Speakers for MDT LCD Monitor Series

Part Number	SPKR-SFL-32 (designed for MDT321S) SPKR-SFL-40 (designed for MDT402S) SPKR-SFL-46 (designed for MDT461S)
Frequency Response	130-20,000 Hz
Sensitivity	90 dB @ 1W @ 1M
Impedance	8 ohms
Power Handling	30 watts program; 50 watts peak
Maximum Output	98 dB
Dimensions	SPKR-SFL-32 (18.9"H x 4.0"W x 2.6"D) SPKR-SFL-40 (22.8"H x 4.0"W x 2.6"D) SPKR-SFL-46 (25.8"H x 4.0"W x 2.6"D)
Weight	Approximately 7-10lb each (packaged in pairs 14-22lbs)



System Configuration	2-way display-mounted loudspeaker
Components and Loading	(2) 3-1/2" woofers; (1) 3/4" soft-dome tweeter
Cabinet Type	Sealed box
Enclosure Material	Cold-rolled steel, ABS endcaps
Finish	Black
Connectors	Dual spring clips (for bare wire or banana plugs)
Suspension Hardware	Integral MonoRail and mounting kit for display mounting
Grill	Integral cloth (Black)

Mitsubishi Digital Electronics America, Inc.
Presentation Products Division
9351 Jeronimo Road, Irvine CA 92618
(888) 307-0349
Email: ppdinfo@mdea.me.com
www.mitsubishi-presentations.com

Technical Support
(888) 307-0309
Email: tsupport@mdea.me.com

Canada
Mitsubishi Electric Sales Canada, Inc.
Information Technology Group
Markham, Ontario
(905) 475-7728
www.mitsubishielectric.com