

Mitsubishi Optional Lens Specifications

XD3200, WD3300, XD3500, XD8100, WD8200, UD8350, UD8400	
OL-XD2000SZ (attached Standard lens)	
Type	Short Throw Zoom Lens (Short Throw Conversion Lens for Standard Lens)
Focal Length	19.6 - 26.5 mm cf. Standard Lens 24.5 - 33.1mm
F Number	F 2.0 - 2.4
Focus/Zoom	Motorized Focus & Zoom (when attached to Standard Lens)
Throw Ratio	
XD2000/XD1000/XD3200/XD8100/XD8000	1.3 - 1.9 (2.7 - 3.8 m@100") cf. Standard Lens 1.7 - 2.4 (3.5 - 4.8 m@100")
WD2000/WD3300/WD8200	1.3 - 1.9 (3.0 - 4.1 m@100") cf. Standard Lens 1.7 - 2.4 (3.8 - 5.2 m@100")
GH-8800	1.4 - 1.9 (3.0 - 4.2 m@100") cf. Standard Lens 1.7 - 2.4 (3.9 - 5.3 m@100")
UD8400	1.3 - 1.8 (2.8 - 3.9 m@100") cf. Standard Lens 1.7 - 2.3 (3.6 - 4.9 m@100")
Off set axis	
XD2000/XD1000/XD3200/XD8100/XD8000	V Shift 1:1 - 12:-1, H Shift Width +/-10%
WD3300/WD8200	V Shift 1:1 - 5.5:-1, H Shift Width +/-10%
WD2000	V Shift 1:1 - 4.5:-1, H Shift Width +/-10%
GH-8800	V Shift 1:1 - 4.3:-1, H Shift Width +/-10%
UD8400	V Shift 1:1 - 6.3:-1, H Shift Width +/-9%

XD3200, WD3300, XD3500, XD8100, WD8200, UD8350, UD8400	
OL-XD2000LZ (attached Standard lens)	
Type	Long Throw Zoom Lens (Long Throw Conversion Lens for Standard Lens)
Focal Length	32.4 - 40.5 mm cf. Standard Zoom Lens 24.5 - 33.1mm
F Number	F 2.1 - 2.4
Focus/Zoom	Motorized Focus & Zoom (when attached to Standard Lens)
Throw Ratio	
XD2000/XD1000/XD3200/XD8100/XD8000	2.2 - 2.9 (4.6 - 5.8 m@100") cf. Standard Lens 1.7 - 2.4 (3.5 - 4.8 m@100")
WD2000/WD3300/WD8200	2.2 - 2.9 (4.9 - 6.2 m@100") cf. Standard Lens 1.7 - 2.4 (3.8 - 5.2 m@100")
GH-8800	2.3 - 2.9 (5.0 - 6.4 m@100") cf. Standard Lens 1.7 - 2.4 (3.9 - 5.3 m@100")
UD8400	2.2 - 2.7 (4.7 - 5.9 m@100") cf. Standard Lens 1.7 - 2.3 (3.6 - 4.9 m@100")
Off set axis	
XD2000/XD1000/XD3200/XD8100/XD8000	V Shift 1:1 - 12:-1, H Shift Width +/-10%
WD3300/WD8200	V Shift 1:1 - 5.5:-1, H Shift Width +/-10%
WD2000	V Shift 1:1 - 4.5:-1, H Shift Width +/-10%
GH-8800	V Shift 1:1 - 4.3:-1, H Shift Width +/-10%
UD8400	V Shift 1:1 - 6.3:-1, H Shift Width +/-9%

XD3200, WD3300, XD3500, XD8100, WD8200, UD8350, UD8400	
OL-XD2000TZ	
Type	Tele Throw Zoom Lens
Focal Length	40.7 - 65.1 mm cf. Standard Lens 24.5 - 33.1mm
F Number	F 2.2 - 2.7
Focus/Zoom	Motorized Focus & Zoom
Throw Ratio	
XD2000/XD1000/XD3200/XD8100/XD8000	2.9 - 4.7 (5.8 - 9.6 m@100") cf. Standard Lens 1.7 - 2.4 (3.5 - 4.8 m@100")
WD2000/WD3300/WD8200	2.9 - 4.7 (6.3 - 10.3 m@100") cf. Standard Lens 1.7 - 2.4 (3.8 - 5.2 m@100")
GH-8800	2.9 - 4.8 (6.5 - 10.6 m@100") cf. Standard Lens 1.7 - 2.4 (3.9 - 5.3 m@100")
UD8400	2.8 - 4.5 (6.0 - 9.8 m@100") cf. Standard Lens 1.7 - 2.3 (3.6 - 4.9 m@100")
Off set axis	
XD2000/XD1000/XD3200/XD8100/XD8000	V Shift 1:1 - 12:-1, H Shift Width +/-10%
WD3300/WD8200	V Shift 1:1 - 5.5:-1, H Shift Width +/-10%
WD2000	V Shift 1:1 - 4.5:-1, H Shift Width +/-10%
GH-8800	V Shift 1:1 - 4.3:-1, H Shift Width +/-10%
UD8400	V Shift 1:1 - 6.3:-1, H Shift Width +/-9%

XD3200, WD3300, XD3500, XD8100, WD8200, UD8350, UD8400	
OL-XD8000UZ	
Type	Ultra Tele Throw Zoom Lens
Focal Length	64.5-125.5 mm cf. Standard Lens 24.5 - 33.1mm
F Number	F 2.8
Focus/Zoom	Motorized Focus & Zoom
Throw Ratio	
XD3200/XD8100/XD8000	4.7 - 9.0 (9.5 - 18.4 m@100") cf. Standard Lens 1.7 - 2.4 (3.5 - 4.8 m@100")
WD3300/WD8200	4.8 - 9.2 (10.2 - 19.7 m@100") cf. Standard Lens 1.7 - 2.4 (3.8 - 5.2 m@100")
GH-8800	4.8 - 9.2 (10.5 - 20.3 m@100") cf. Standard Lens 1.7 - 2.4 (3.9 - 5.3 m@100")
UD8400	4.5 - 8.7 (9.8 - 18.8 m@100") cf. Standard Lens 1.7 - 2.3 (3.6 - 4.9 m@100")
Off set axis	
XD3200/XD8100/XD8000	V Shift 1:1 - 12:-1, H Shift Width +/-10%
WD3300/WD8200	V Shift 1:1 - 5.5:-1, H Shift Width +/-10%
GH-8800	V Shift 1:1 - 4.3:-1, H Shift Width +/-10%
UD8400	V Shift 1:1 - 6.3:-1, H Shift Width +/-9%

XD3200, WD3300, XD3500, XD8100, WD8200, UD8350, UD8400	
OL-XD2000FR	
Type	Fixed Focal Rear Lens
Focal Length	11.5 mm cf. Standard Lens 24.5 - 33.1mm
F Number	F 2.4
Focus	Motorized Focus
Throw Ratio	
XD2000/XD1000/XD3200/XD8100/XD8000	0.8 (1.6 m @100") cf. Standard Lens 1.7 - 2.4 (3.5 - 4.8 m@100")
WD2000/WD3300/WD8200	0.8 (1.8 m @100") cf. Standard Lens 1.7 - 2.4 (3.8 - 5.2 m@100")
GH-8800	0.8 (1.8 m @100") cf. Standard Lens 1.7 - 2.4 (3.9 - 5.3 m@100")
UD8400	0.8 (1.7 m @100") cf. Standard Lens 1.7 - 2.3 (3.6 - 4.9 m@100")
Off set axis	1 : 1 (No variable lens shift)



PRESENTATION PRODUCTS

Mitsubishi Electric Visual Solutions America
 Presentation Products Division
 9351 Jeronimo Road
 Irvine, CA92618
 Toll Free: 888-307-0349
 email: pppinfo@mdea.com