



# Wireless MW-2100

Wireless Adapter

The MW-2100 is an **external** compact Wireless Video Adapter that is compatible with Mitsubishi projectors. Compatible with wireless (IEEE 802.11 b/g) computers, **MW-2100** revolutionizes how projectors are used. The adapter connects to a projector's VGA or DVI port and enables a computer to display to the projector without a cable. Presenters no longer are limited by the cable length from the computer to the projector.

This MW-2100 model is codec independent, so all video clips such as browser-based streaming movies, video clips, digital photo slide



## Simple and Easy Setup

Setup is similar to a WiFi Hotspot connection. When powering on, the MW-2100 is seen as an available wireless network connection on the systems network settings. Users just simply run the installation CD\* on their system and load the necessary drivers to their system. Upon the completion of this quick and simple installation, you just have to launch the MW-2100 application to make a wireless connection. There's no need to set up IP address, DHCP settings, etc. It's that simple and easy to setup.

\* - Installation files will also be available for download via Mitsubishi Website

## Accessibility

Sharing **MW-2100** among users is straight forward. To allow the second user to gain access to the projector, the first user simply click on the "Stop Projection" button. The second user then can gain access to the projector by launching the software application.



## General Features

- Ability to view downloaded movies, web-cast or streaming video, digital photos, slide shows, Internet, Word documents, Excel files, PowerPoint, etc.
- Simple hot-spot like setup
- Compatible with DVI and VGA video displays
- Codex agnostic - wirelessly streams all current and future video and audio formats
- Security settings options- WEP: 64/128 bit-Hex or 64/128 bit ASCII, WPA2PSK, or none



# Wireless MW-2100

Wireless Adapter

## Specifications

Interfaces	Video Audio Network Wireless Power	VGA (HD15f), DVI (DVI-I f) 3.5mm stereo mini jack RJ-45 jack Reverse SMA antenna DC-in jack
Memory	Flash/SDRAM SDRAM	8MB/32MB 32MB
Networking	Wireless Wired	802.11b/g (54Mbps) 10/100 fast Ethernet
System Processor	Processor Memory Wireless OS	>Pentium 1.5GHz >512MB 802.11b/g WLAN Windows XP Pro, XP Home, Win 2K w/SP4
Resolutions		640x480, 60/75Hz refresh rate 800x600, 60/75Hz refresh rate 1024x768, 60/75Hz refresh rate
Power Adapter		AC adapter 5V DC/2A
Operating Conditions	Temperature Humidity	41-104°F (5-40°C) 20-85% (non-condensing)
Dimensions/Weight	Product	5.9"x3.1"x1.4" inches / 0.5lb
Regulatory		RoHS, UL/cUL, FCC Part 15 Class B
Package Content		Product, antenna, AC adapter (with US a EUR plugs), CD, Quick Install Guide

